

10/586170

AP20 Rec'd PCT/PI0 17 JUL 2006

**CENTER OFFICE WIDEBAND DEVICE WITH SELF-DETECTION FUNCTION AND  
DETECTING METHOD THEREOF**

**FIELD OF THE INVENTION**

5 [0001] The present invention relates to the field of communication technology, and in particular to a method of center office wideband device correlation detection.

**BACKGROUND OF THE INVENTION**

10 [0002] With the rapid popularization of network technologies and the fast development of multimedia technologies, the user's demand on the bandwidth becomes increasingly higher. The Digital Subscriber Line (DSL) technology has stepped into a stage of high-speed development since the year of 2003, and the number of users of Asymmetric Digital Subscriber Line (ADSL) and Very-High-Data-Rate Digital Subscriber Line (VDSL) are increasing rapidly.

15 Meanwhile, the test and maintenance of the wideband network has become a headache to its operator. Particularly, the wideband network is more complicated and involves more technical intervention in comparison with the conventional narrowband telecommunication network, and therefore the detection and maintenance has become a global problem and seriously restricted the development

20 of the wideband network. Currently, all systems in the market used for the simulation test of the wideband network are individual box-like test devices as shown in Fig. 1. It is required that when the Digital Subscriber Line Access Multiplex (DSLAM) catches a line (disconnects the user inner and outside lines of the DSLAM, and connects the inner line and the outside line to a test bus respectively), the test line is subject to the

25 test by the test device. The test device transmits an ADSL test signal to the caught test line through a simulation module, then analyzes the data obtained from the test so as to get a final result, and processes the test result in the following two ways:

[0003] 1. The test result is passed to a console for display and analysis, and therefore a computer with special software installed is required for the test control, and

30 a person shall be dispatched for the test to the place where the device is located.

[0004] 2. The data obtained from the test are transmitted through a network interface to a remote terminal where the data are analyzed and processed, and therefore a computer installed with special software is required for the test control and the display, and an independent public network IP address is also required.

5 [0005] Thus a special test device has to be added, resulting in the increased cost and difficulty for the networking.

[0006] Current test devices are rather expensive, and particularly, a country region can hardly afford such expensive test systems.

10 [0007] The detection through a test device needs special software and computer to process and display a test result or supports a remote test, which requires that a public network IP address shall be assigned to the test device, and thus occupies related resources. Moreover, the maintenance workload is so large due to thousands of failure reports from DSL users that it is difficult to deal with the reports duly and the operation cost is high.

15 [0008] Only ADSL ports can be tested, but VDSL ports cannot be tested, otherwise an additional VDSL test device shall be added.

[0009] And the test operations are complicated.

### **SUMMARY OF THE INVENTION**

20 [0010] An embodiment of the present invention provides a center office wideband device with a self-detection function and a method thereof that can locate and judge quickly a port failure by means of the center office wideband device without any additional special test device.

25 [0011] The center office wideband device with a self-detection function may comprise a plurality of XDSL center office ports, where at least one control switch group may be provided, and the XDSL center office ports are connected through the control switch group to outside lines with which remote user devices are connected.

[0012] The control switch group connects or disconnects one or more of the XDSL center office ports based upon a control signal transmitted from the center office wideband device, so as to exchange the outside lines with which two of the XDSL

center office ports are connected.

[0013] Optionally, the control switch group may be a relay group or an analog switch group.

[0014] Optionally, the XDSL center office ports may be ADSL center office ports or  
5 VDSL center office ports.

[0015] The detecting method using the above center office wideband may comprise the steps of:

[0016] searching for a corresponding relationship between a failed-line number and a center office port based upon the failed-line number contained in failure information  
10 reported from a user to determine a specific port position of a failed line in the center office wideband device;

[0017] searching and determining a normal port at which there is no service stream at present; and

[0018] controlling the control switch group connected between the center office ports  
15 and the outside lines to be opened or closed based upon a control signal within the center office wideband device, replacing the failed port with the normal port, testing a custom position equipment with which the failed port is originally connected, and thus determining whether the failure results from the port itself or the user side.

[0019] Optionally, the step of controlling the control switch group connected between  
20 the center office ports and the outside lines to be opened or closed based upon a control signal within the center office wideband device and replacing the failed port with the normal port may comprise the steps of:

[0020] controlling the control switch group to disconnect the failed port and the outside line with which the custom position equipment is connected;

25 [0021] connecting the normal port to the outside line; and

[0022] transmitting an activation command by the center office wideband device to activate, with the normal port, the custom position equipment with which the failed port is originally connected.

[0023] Optionally, in the case the normal port, after being connected to the outside

line, is capable to activate the custom position equipment with which the failed port is originally connected, determining that the failure results from the failed port itself; otherwise, determining that the failure results from a line or user-side failure.

[0024] Since the embodiments of the present invention have improved the existing  
5 center office wideband device, and the improved center office wideband device can locate and judge quickly a port failure without any additional special test device. Moreover, since the operating person can operate the device at the center office or remotely without the need of being dispatched to the place where the device is located. Also, the center office wideband device itself is provided with both ADSL ports and  
10 VDSL ports, so it is possible to find either an operative ADSL port or an operative VDSL port so as to test the Custom Position Equipment (CPE) of the failed port.

#### **BRIEF DESCRIPTIONS OF THE DRAWINGS**

[0025] Fig.1 is a schematic diagram of the networking of the conventional Central Office (CO) wideband device plus a test system;

15 [0026] Fig.2 is a schematic diagram of the connection of ADSL/VDSL CO ports in the conventional device and a user MODEM; and

[0027] Fig.3 is a schematic diagram of the connection of ADSL/VDSL CO ports in a device according to an embodiment of the present invention and a user MODEM.

#### **DETAILED DESCRIPTIONS OF THE EMBODIMENTS**

20 [0028] In the following, embodiments of the present invention will be described in detail with reference to the drawings.

[0029] It is necessary to adapt the conventional center office (CO) wideband device into a device with a self-detection function according to the embodiment of the present invention. As shown in Fig. 2, each CO port in the conventional CO wideband device  
25 is connected to a remote user MODEM directly through an outside line, and the connection is one-to-one corresponding and fixed. That is, a CO port P1 can be connected only to a Modem with which an outside line of Line 1 is connected, and so on. Fig. 3 shows the adapted device which comprises several ADSL CO ports or several VDSL CO ports and at least one switch control group arranged between the

CO ports and outside lines connected to remote user Modems. The respective ADSL/VDSL CO ports are connected to the outside lines through the control switch group, which may be a relay group or an analog switch group. Upon a control command provided by a control system within the device, the relay group or the  
5 analog switch group is operated to disconnect any of the ADSL/VDSL CO ports and exchange the outside lines with which any two of the ADSL CO ports are connected or exchange the outside lines with which any two of the VDSL CO ports are connected. For example, it is assumed both CO Port 1 and CO Port 2 as shown in Fig. 3 are ADSL ports, and CO Port 1 and CO Port 2 are respectively connected to Line 1 and  
10 Line 2 via the relay group. When the control system within the device transmits the control command to the relay group, CO Port 1 is disconnected from Line 1, CO Port 2 is disconnected Line 2, and CO Port 1 is connected to Line 2, and CO Port 2 is connected to Line 1.

[0030] The adapted CO broadband device can thus detect a failure phenomenon of  
15 its own port, locate the failure and determine a specific reason for the failure. The detecting and locating method according to an embodiment of the present invention may be such a procedure that comprises the following essential steps.

[0031] A. Based upon a failed-line number contained in failure information reported from the user, the procedure searches for a corresponding relationship between the  
20 line number and the CO port, and determines a specific port position of the failed line in the CO wideband device, where the port is called the failed port. The reason for the failure can be a failure at the port itself or at the user side, and the failure at the user side comprises a line failure and a User Position Equipment (CPE) failure.

[0032] B. A maintenance person from the center office searches on the console to  
25 determine a normal port at which there is no service stream at present.

[0033] C. Upon a command from the control system within the device, the control switch group connected between the CO ports and the outside lines is operated for example to be opened or closed, the failed port is replaced with the determined normal port so as to test the CPE with which the failed port is originally connected,

and thus it can be determined whether the failure results from the port itself or the user side.

[0034] Further, Step C comprises the following steps.

[0035] C1. The process controls the control switch group to disconnect the failed  
5 port and Line 1 with which the CPE is connected and to disconnect the normal port  
and Line 2 with which the CPE is connected.

[0036] C2. The process connects the normal port to Line 1.

[0037] C3. The control system within the device transmits an activation command  
to activate, with the normal port, the CPE with which the failed port is originally  
10 connected. If the normal port, after being connected to Line 1, is capable to activate  
the CPE with which the failed port is originally connected, then the failure may be due  
to the failed port itself. If the normal port, after being connected to Line 1, is still not  
capable to activate the CPE with which the failed port is originally connected, then the  
failure may be due to the line or the CPE.

15 [0038] In the XDSL specifications of some telecommunication operators, it is  
required that a central office wideband device (DSLAM) shall be provided with the  
function of line catching, which thus guarantees the implementation of the present  
invention in terms of hardware.

[0039] The above embodiments of the present invention require no additional  
20 hardware device and simply make use of the ADSL/VDSL ports with which the device  
has been provided already. Particularly, the CPE of the failed port is connected to a  
known CO port through the control switch, and the normal CO port is used to activate  
the CPE with which the failed port is connected. For the port under test, the data can  
be obtained when the CPE under test is activated just as in a normal service routine.  
25 If the CPE with which the failure port is connected is activated successfully, then it can  
be substantially determined that the failure may be due to the port itself; otherwise, the  
failure may be more likely due to a line or CPE error.

[0040] Since the normal port may be found on the DSLAM device, it can be ensured  
that the tested port itself has nothing wrong.

[0041] A DSLAM network is located at edge devices and thus is mostly not placed in a central machine room. Particularly in a country region, the machine room is located in a harsh environment. Moreover, both dust particles in the north and humidity in the south may cause a short circuit of a single board resulting in a failure of a separate port. Therefore, the embodiments of the present invention can facilitate locating the problem of the port failure.

[0042] It can be seen from current statistics that once a XDSL service is started, in the case the failure reported from the user is not a line failure but a port failure or a CPE configuration failure, the embodiments of the present invention can rapidly locate the port failure or the user-side failure.

[0043] According to the embodiments of the present invention, not only the ADSL ports but also the VDSL ports can be detected. Since the CO wideband device itself is provided with both ADSL ports and VDSL ports, it is thus possible to find either an operative ADSL port or an operative VDSL port so as to test the CPE of the failed port.

[0044] It shall be appreciated that various changes or modifications can be made to the disclosed embodiments without departing from the scope of the present invention as defined by the accompanied claims.

## CLAIMS

### What is claimed is:

1. A center office wideband device with a self-detection function, with a plurality of XDSL center office ports, comprising at least one control switch group is provided, and the XDSL center office ports are connected through the control switch group to outside lines with which remote user devices are connected; and the control switch group connects or disconnects one or more of the XDSL center office ports based upon a control signal transmitted from the center office wideband device, so as to exchange the outside lines with which two of the XDSL center office ports are connected.

2. The device according to claim 1, wherein the control switch group is a relay group or an analog switch group.

3. The device according to claim 1 or 2, wherein the XDSL center office ports are ADSL center office ports or VDSL center office ports.

4. A detecting method using a center office wideband device according to claim 1, comprising the steps of:

searching for a corresponding relationship between a failed-line number and a center office port based upon the failed-line number contained in failure information reported from a user to determine a specific port position of a failed line in the center office wideband device;

searching and determining a normal port at which there is no service stream at present; and

controlling the control switch group connected between the center office ports and the outside lines to be opened or closed based upon a control signal within the center office wideband device, replacing the failed port with the normal port, testing a custom position equipment with which the failed port is originally connected, and thus determining whether the failure results from the port itself or the user side.

5. The method according to claim 4, wherein the step of controlling the control switch group connected between the center office ports and the outside lines



to be opened or closed based upon a control signal within the center office wideband device and replacing the failed port with the normal port comprising the steps of:

controlling the control switch group to disconnect the failed port and the outside line with which the custom position equipment is connected;

5 connecting the normal port to the outside line; and

transmitting an activation command by the center office wideband device to activate, with the normal port, the custom position equipment with which the failed port is originally connected.

10 6. The method according to claim 5, wherein in the case the normal port, after being connected to the outside line, is capable to activate the custom position equipment with which the failed port is originally connected, determining that the failure results from the failed port itself; otherwise, determining that the failure results from a line or user-side failure.

### ABSTRACT

The present invention discloses a center office wideband device with a self-detection function and a method of detecting XDSL ports, where at least one control switch group is provided in the device. The respective XDSL center office ports are connected through the control switch group to outside lines with which remote user devices are connected, and the control switch group receives a control command transmitted from a control system within the device, disconnects any of the XDSL center office ports based upon the control command, and exchanges the outside lines with which two of the XDSL center office ports are connected. Through the control switch group, any of the XDSL center office ports is disconnected, or the outside lines with which two of the XDSL center office ports are connected are exchanged. Thus, upon locating a failed CO port, a normal port within an operative device may be used to replace a CPE with which the failed port is originally outside-connected, and it may be determined whether the failed port results from the port itself or the user side. It is possible to locate and judge the port failure quickly without an additional special test system, and hence the cost can be reduced.

(Fig. 3)